



# HIGH PRESSURE HOSE 3000 BAR



## ORDER DENOMINATION:

„High Pressure hose, .. m long, with cap nut on both ends G1/4“,  
**Art.Nr. 2-00578-XXXX** The last 4 digits define the length, e.g. 3m: 2-00578-0003.

## LENGTHS ON STOCK:

0,5m; 1m; 2m; 3m; 4m; 5m; 6 m All other lengths can be delivered upon request.

## DELIVERY STATE:

Completely assembled, bleded and filled with oil.

*Standard filling is hydraulic oil. Other liquids are available upon request.*

All hoses are equipped with a protection hose. The data printed on the high pressure hose, i.e.: „EN/A578/5/XQJJ/PN3000“ are exclusively related to the high-pressure hose.

The minimal bending radius of the high pressure hose is 175 mm.

## TECHNICAL DATA:

### High Pressure hose

max. operating pressure:	3.000 bar
Test pressure:	4.650 bar
min. burst pressure:	6.200 bar
Inner diameter:	5,0 mm
Major diameter:	10,9 mm
Hose core:	POM
Pressure bearers:	6 coiling shifts of corrosion proof spring steel wire
Top layer:	PA, Nylon 11/12
Protection hose:	PVC
Weight:	0,45 kg/m

